

Product Finish: Brushed nickel

Product code: AT1101
EAN13 barcode: 5060048381047




Product features:

- Metal & ABS construction
- Custom designed for lower to mid pressures
- Connects to any water supply, works independently of the tap
- Single spray pattern showerhead
- Grey nylon spout hose for stylish durability

Additional information / Parts included:

Note: the image shown may not reflect the product finish, chrome finish is typically depicted.

Product dimensions:



- Overall Height / projection: 158 mm
- Exit reach: 0-1200 mm
- Exit height: 140 mm
- Centre distance(s):


- Base diameter(s): 50 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 40 mm

- Spout diameter: n/a mm
- Spout aerator size: n/a

Packaged properties:

- Box length: 420mm
- Box depth: 75mm
- Box width: 240mm
- Units per outer: 5
- Tap only weight: 0.08kg
- Boxed weight: 1.12kg

Product flow characteristics:



- Min / Max water pressure: 0.50 / 2 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 09.40

- Control valve type: Trigger
- Product flow characteristics: Single flow
- Non return valve(s): Integral to spray head

- Aerator type: Sprayhead only
- Accepts revolve / spray areator: No
- Spout connection method: N/a

- Tail pipe inlet / outlet size: 1/2" Male / 1/2" BSP Female
- Inlet pipe type / length: flexible stainless braided hose / 1700 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year