

Product Finish: Chrome with white detail

Product code: AT1128
EAN13 barcode: 5060048381443



Note: the image shown may not reflect the product finish, chrome finish is typically depicted.


Product features:

- Metal & acrylic handle construction
- Custom designed for lower to mid pressures
- Fixing kit designed for thicker surface depths
- Multiple finish options for perfect coordination
- Quarter turn handle action for precise flow control

Additional information / Parts included:

Low pressure flow straightener included

Product dimensions:



- Overall Height / projection: 270 mm
- Exit reach: 200 mm
- Exit height: 185 mm
- Centre distance(s):


- Base diameter(s): 42 mm
- Recommended hole diameter: Ø 35 mm
- Max. surface depth: 55 mm

- Spout diameter: 20/22 mm
- Spout aerator size: 22f

Packaged properties:

- Box length: 430mm
- Box depth: 70mm
- Box width: 340mm
- Units per outer: 5
- Tap only weight: 2.54kg
- Boxed weight: 3.04kg

Product flow characteristics:



- Min / Max water pressure: 0.40 / 5.5 bar
- Recommended / Max water temperature: 46°C / 70°C
- Part G - Mixed flow rate at 3 bar (litres / min): 17.97

- Control valve type: Ceramic disc QT
- Product flow characteristics: Single flow
- Non return valve(s): Integral to hot & cold inlets

- Aerator type: Plastic mesh diffuser
- Accepts revolve / spray areator: Yes
- Spout connection method: Grub screw

- Tail pipe inlet / outlet size: 1/2" BSP Male
- Inlet pipe type / length: fixed threaded inlets / 75 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year